

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 29.08.2016

Revision: 25.08.2016

### 1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Bead Sealer**
- **Article number:** 600 5002 , 600 5002B , 600 5002G
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Rubber Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
HAG SAL  
Seaside Dora Highway  
Po Box 80269  
Beirut-Lebanon  
Tel: +961 1 241900

### 2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H400, H410.



flame

Flam. Liq. 2      H225 Highly flammable liquid and vapour.



environment

Aquatic Acute 1      H400 Very toxic to aquatic life.

Aquatic Chronic 1      H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2      H315 Causes skin irritation.

Skin Sens. 1      H317 May cause an allergic skin reaction.

STOT SE 3      H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R65:      Harmful: may cause lung damage if swallowed.



Xi; Irritant

R38:      Irritating to skin.

(Contd. on page 2)

# Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 1)



Xi; Sensitising

R43: May cause sensitisation by skin contact.



F+; Highly flammable

R11: Highly flammable.



N; Dangerous for the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

**Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

**Hazard pictograms**

This pictogram only applicable for EU regulations. Not for use in the United States (OSHA GHS).



GHS02 GHS07 GHS09

**Signal word** Danger**Hazard-determining components of labelling:**

heptane

tar, pine

Natural rubber latex

**Hazard statements**

The following Hazard Statements are applicable only to the EU regulations and not the US GHS regulation: H410.

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 3)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 2)

**· Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P280 Wear protective gloves / eye protection.
- P233 Keep container tightly closed. P264 Wash thoroughly after handling. P261 Avoid breathing mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.


**· Hazard description:**

**· WHMIS-symbols:**

- B2 - Flammable liquid
- D2B - Toxic material causing other toxic effects



**· NFPA ratings (scale 0 - 4)**



**· HMIS-ratings (scale 0 - 4)**



\* - Indicates a long term health hazard from repeated or prolonged exposures.

**· HMIS Long Term Health Hazard Substances**

None of the ingredients is listed.

**· 2.3 Other hazards**

**· Results of PBT and vPvB assessment**

- PBT: Not applicable.
- vPvB: Not applicable.

### 3 Composition/information on ingredients

**· 3.2 Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 4)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS













Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 3)

**· Dangerous components:**

CAS: 142-82-5 EINECS: 205-563-8 Index number: 601-008-00-2	heptane  Xn R65;  Xi R38;  F R11;  N R50/53 R67  Flam. Liq. 2, H225  Asp. Tox. 1, H304  Aquatic Acute 1, H400; Aquatic Chronic 1, H410  Skin Irrit. 2, H315; STOT SE 3, H336	80-85%
CAS: 9006-04-6	Natural rubber latex  Xi R43  Skin Sens. 1B, H317	3-8%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black  Xn R40 Carc. Cat. 3  Carc. 2, H351	0-5%

**· Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

**· 4.1 Description of first aid measures**

**· General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

**· After inhalation:**

Supply fresh air; consult doctor in case of complaints.

Supply fresh air or oxygen; call for doctor.

In case of irregular breathing or respiratory arrest provide artificial respiration.

**· After skin contact:**

Immediately remove any clothing soiled by the product.

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

**· After eye contact:**

Remove contact lenses if worn, if possible.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**· After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

**· 4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty

Dizziness

Coughing

(Contd. on page 5)

**Safety Data Sheet**  
according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 4)

Irritant to skin and mucous membranes.  
Irritant to eyes.  
Gastric or intestinal disorders when ingested.  
Disorientation

· **Hazards**

Danger of impaired breathing.  
May be harmful in contact with skin.  
May be harmful if inhaled.  
Repeated exposure may cause skin dryness or cracking.  
Vapours may cause drowsiness and dizziness.

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.  
If necessary oxygen respiration treatment.

**5 Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water
- **5.2 Special hazards arising from the substance or mixture**  
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information** Eliminate all ignition sources if safe to do so.

**6 Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation  
Keep away from ignition sources.  
Protect from heat.
- **6.2 Environmental precautions:**  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.
- **6.3 Methods and material for containment and cleaning up:**  
Allow to solidify. Pick up mechanically.  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Pick up mechanically.  
Dispose contaminated material as waste according to item 13.  
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.

(Contd. on page 6)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

(Contd. of page 5)

### 7 Handling and storage

- **7.1 Precautions for safe handling** Use only in well ventilated areas.
- **Information about fire - and explosion protection:**
  - Keep ignition sources away - Do not smoke.
  - Protect against electrostatic charges.
  - Flammable gas-air mixtures may form in empty receptacles.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
  - Store in a cool location.
  - Provide ventilation for receptacles.
  - Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
  - Store away from foodstuffs.
  - Store away from oxidizing agents.
- **Further information about storage conditions:**
  - Store in cool, dry conditions in well sealed receptacles.
  - Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

### 8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**142-82-5 heptane**

IOELV (EU)	Long-term value: 2085 mg/m <sup>3</sup> , 500 ppm
PEL (USA)	Long-term value: 2000 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> , 85 ppm Ceiling limit: 1800* mg/m <sup>3</sup> , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2,045 mg/m <sup>3</sup> , 500 ppm Long-term value: 1,635 mg/m <sup>3</sup> , 400 ppm

(Contd. on page 7)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 6)

**9006-04-6 Natural rubber latex**

TLV (USA) Long-term value: 0,0001\* mg/m<sup>3</sup>  
Skin; (SEN) NIC-DSEN, RSEN;\* inh. fraction

EL (Canada) Long-term value: 0,001 mg/m<sup>3</sup>  
inhalable, Skin; S

EV (Canada) Long-term value: 0,001 mg/m<sup>3</sup>  
as total proteins, inhalable, Skin

**1333-86-4 Carbon black**

PEL (USA) Long-term value: 3,5 mg/m<sup>3</sup>

REL (USA) Long-term value: 3,5\* mg/m<sup>3</sup>  
\*0,1 in presence of PAHs; See Pocket Guide Apps.A+C

TLV (USA) Long-term value: 3\* mg/m<sup>3</sup>  
\*inhalable fraction

EL (Canada) Long-term value: 3 mg/m<sup>3</sup>  
IARC 2B

EV (Canada) Long-term value: 3,5 mg/m<sup>3</sup>

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

• **8.2 Exposure controls**

• **Personal protective equipment:**

• **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

• **Respiratory protection:**

Not required under normal conditions of use.

Use suitable respiratory protective device when high concentrations are present.

Use suitable respiratory protective device when aerosol or mist is formed.

For spills, respiratory protection may be advisable.

NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used.

• **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be

(Contd. on page 8)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 7)

- checked prior to the application.
- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**  
No further relevant information available.
- **Risk management measures**  
See Section 7 for additional information.  
No further relevant information available.

### 9 Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Viscous
Colour:	Black
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.

- **Change in condition**

Melting point/Melting range:	Not Determined.
Boiling point/Boiling range:	205 ° F / 96 °C

Flash point:	16 ° F / -9 °C
Flammability (solid, gaseous):	Not applicable.
Auto/Self-ignition temperature:	419 ° F / 215 °C
Decomposition temperature:	Not determined.

- **Self-igniting:** Product is not self-igniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

- **Explosion limits:**

Lower:	1,1 Vol %
Upper:	6,7 Vol %

- **Vapour pressure at 20 °C:** 48 hPa

- **Density:** Not determined.

(Contd. on page 9)



## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 8)

- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic at 20 °C:** > 20,5 mm<sup>2</sup>/s (Predicted)
- **9.2 Other information** No further relevant information available.

### 10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** Keep away from heat and direct sunlight.
- **10.3 Possibility of hazardous reactions**
  - Flammable.
  - Reacts violently with oxidizing agents.
  - Used empty containers may contain product gases which form explosive mixtures with air.
  - Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomised.
  - Toxic fumes may be released if heated above the decomposition point.
- **10.4 Conditions to avoid**
  - Keep away from heat and direct sunlight.
  - Keep ignition sources away - Do not smoke.
  - Store away from oxidizing agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

### 11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

**142-82-5 heptane**

Oral LD50 > 5000 mg/kg (rat) (Estimate)

Inhalative LC50/4h 103 mg/l (rat)

**1333-86-4 Carbon black**

Oral LD50 10000 mg/kg (rat)

- **Primary irritant effect:**
  - on the skin:** Irritant to skin and mucous membranes.
  - on the eye:** No irritating effect.
- **Sensitization:** Sensitization possible through skin contact.

(Contd. on page 10)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 9)

**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

Toxic and/or corrosive effects may be delayed up to 24 hours.

**Acute effects (acute toxicity, irritation and corrosivity):**

May be harmful if swallowed.

May be harmful in contact with skin.

May be harmful if inhaled.

Vapours have narcotic effect.

**Sensitisation:** Sensitization possible by skin contact.**Repeated dose toxicity:**

Repeated exposure may cause skin dryness or cracking.

May cause damage to organs through prolonged or repeated exposure.

Repeated exposures may result in skin and/or respiratory sensitivity.

## 12 Ecological information

**12.1 Toxicity**

**Aquatic toxicity:** Toxic for aquatic organisms

**12.2 Persistence and degradability** Easily biodegradable

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**Ecotoxicological effects:****Remark:**

Very toxic for fish

The product is oxygen-consuming. The declared action may be partly caused by lack of oxygen.

**Additional ecological information:****General notes:**

Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

**12.5 Results of PBT and vPvB assessment**

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

(Contd. on page 11)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 10)

### 13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. Contact waste processors for recycling information. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **14.1 UN-Number**
- **DOT, ADR, IMDG, IATA**
- **14.2 UN proper shipping name**
- **DOT**
- **ADR**
- **IMDG, IATA**
- **14.3 Transport hazard class(es)**

UN1206

Heptanes, mixture  
1206 HEPTANES, mixture, ENVIRONMENTALLY HAZARDOUS  
HEPTANES, mixture

- **DOT**



- **Class**
- **Label**

3 Flammable liquids.  
3

- **ADR**



- **Class**
- **Label**

3 (F1) Flammable liquids.  
3

- **IMDG, IATA**



- **Class**

3 Flammable liquids.

(Contd. on page 12)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 11)

- **Label** 3
- **14.4 Packing group**
- **DOT, ADR, IMDG, IATA** II
- **14.5 Environmental hazards:**
- **Marine pollutant:** No
- **Special marking (ADR):** Symbol (fish and tree)
- **14.6 Special precautions for user** Warning: Flammable liquids.
- **Danger code (Kemler):** 33
- **EMS Number:** F-E,S-D
- **14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.
- **Transport/Additional information:**

- **ADR**
- **Limited quantities (LQ)** 1L
- **Transport category** 2
- **Tunnel restriction code** D/E
- **UN "Model Regulation":** UN1206, HEPTANES, mixture, ENVIRONMENTALLY HAZARDOUS, 3, II

### 15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65 (California):**

· **Chemicals known to cause cancer:**

1333-86-4	Carbon black
-----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 13)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 12)

· **Carcinogenic Categories**

· **EPA (Environmental Protection Agency)**

142-82-5	heptane	D
----------	---------	---

· **IARC (International Agency for Research on Cancer)**

1333-86-4	Carbon black	2B
-----------	--------------	----

· **TLV (Threshold Limit Value established by ACGIH)**

1333-86-4	Carbon black	A4
-----------	--------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black	
-----------	--------------	--

· **Canada**

· **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

· **Canadian Ingredient Disclosure list (limit 0.1%)**

None of the ingredients is listed.

· **Canadian Ingredient Disclosure list (limit 1%)**

142-82-5	heptane	
----------	---------	--

1333-86-4	Carbon black	
-----------	--------------	--

· **Other regulations, limitations and prohibitive regulations**

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- R11 Highly flammable.
- R38 Irritating to skin.
- R40 Limited evidence of a carcinogenic effect.
- R43 May cause sensitisation by skin contact.

(Contd. on page 14)

## Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and  
GHS

Printing date 29.08.2016

Revision: 25.08.2016

**Trade name: Bead Sealer**

(Contd. of page 13)

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

• **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B

Carc. 2: Carcinogenicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - Acute Hazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1